

1000 liter tank i Rostfritt 304



192,000,00 kr /st exkl moms

Article type: second-hand mixing tank

Additional information: tank has never been used; welds polished Ra 0.8; agitator completely stainless-steel; we can't give any guarantees about the agitator

Volumetric volume (L): 1.000 L

Max. density P (kg/m³): 1.200

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 80 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: conical 15 °

Shape of tank: cylindrical

Bottom type: conical 15

Total discharge: yes

Fixation points: 3 non adjustable feet

Legs: Set of baseplates and adjusting pieces included

Spray ball: RVS 304

Manway(s): RVS 304

Gasket manway(s): unknown

Fixation point(s): RVS 304

Wet parts agitator(s): SS AISI 304 (V2A)

Suitable for food industry: no

Documents included: no

Technical drawing included: yes

Registration plate on the tank: no

Flange for agitator: yes

CIP spray ball: no

Tank outlet: inside Ø 50 mm

Outlet type: DIN11850 male

Total outlet valve: no

Adjustable legs: yes

Agitator: yes

Agitator type: propeller agitator

Position engine: at the top

Number of revolutions: 1.425

Power: 2,20

Voltage: three-phase

Top: 3 mm

Cylinder: 3 mm

Bottom: 3 mm

Distance from outlet to ground: 280 mm

Outer diameter tank: 1.450 mm

Cylinder height: 630 mm

Total height of tank: 2.100 mm

Total outer width: 1.600 mm

Total outer length: 1.900 mm

Empty weight tank: 350

SKU: 9473

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Max. arbetstemperatur: 80 °C

Maximal densitet för produkten: 1200

Mobil tank: Nej

Övrig information: tank has never been used: welds polished Ra 0.8; agitator completely stainless-steel; we can't give any guarantees about the agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical 15

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 1000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Ja

Märkskylt: Nej

Tankutlopp: inside Ø 50 mm

Teknisk ritning finns: Ja

Utloppstyp: DIN11850 male

Utloppsventil: Nej

Översikt material

Material: Rostfritt 304

Fixeringspunkt(er): RVS 304

Material vätskeberörd del på omrörare: SS AISI 304 (V2A)

Dimensioner av tank

Cylinderhöjd: 630 mm

Mått utlopp till marken: 280 mm

Total höjd: 2.100 mm

Ytterdiameter: 1.450 mm

Omrörare

Kraft (kW): 2,20

Position motor: at the top

Typ av omrörare: propeller agitator

Varvtal: 1.425

Spänning (Volt): three-phase

Tjocklek på tank

Botten: 3 mm

Cylinder: 3 mm

Topp: 3 mm

Mer

Isolerad: Nej

Vikt: 350