

1000 liter tank i Syrafast 316



197,000,00 kr /st exkl moms

Additional information: Outlet DN 60 DIN 11851; reinforcement ribs inside under the upper bottom (removable); 2 fork pockets on the outside of the lower bottom; slight adhesions (pickling residues) inside the tank

Volumetric volume (L): 1.000 L

Pressure in tank: ATM - atmosferic
Max. temperature (°C): 180 °C
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes
Insulation: yes
Mobile tank: no

Total discharge: no
Max Overpressure: 2 Bar
Max. working temperature: 180 °C
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: yes
Internal diameter tank: 1.200 mm
Outer diameter tank: 1.400 mm
Total height of tank: 1.520 mm

SKU: 283021

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 180 °C

Mobil tank: Nej

Övrig information: Outlet DN 60 DIN 11851; reinforcement ribs inside under the upper bottom (removable); 2 fork pockets on the outside of the lower bottom; slight adhesions (pickling residues) inside the tank; we

Övrig information2: can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Total urtappning: Nej

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Ja

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Invändig diameter: 1.200 mm

Total höjd: 1.520 mm

Ytterdiameter: 1.400 mm

Mer

Isolerad: Ja
