

## 10000 liter tank i Syrafast 316



**391,000,00 kr /st exkl moms**

**Additional information:** Total height as per drawing

**Volumetric volume (L):** 10.000 L

**Pressure in tank:** ATM - atmosferic

**Max. temperature (°C):** 90 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 38 L

**Max Overpressure:** 3 Bar

**Max. working temperature:** 90 °C

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** yes

**Position of manway:** in the bottom

**Outlet of tank:** 76

**Internal diameter tank:** 2.050 mm

**Outer diameter tank:** 2.200 mm

**Cylinder height:** 3.000 mm

**Total height of tank:** 4.800 mm

**SKU:** 454394

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosfERIC

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 90 °C

Mobil tank: Nej

Övrig information: Total height as per drawing; we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 10000

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Ja

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 3.000 mm  
Invändig diameter: 2.050 mm  
Total höjd: 4.800 mm  
Ytterdiameter: 2.200 mm

## Mer

Isolerad: Ja