

118 liter tank i Syrafast 316



60,000,00 kr /st exkl moms

Article type: second-hand mixing tank

Additional information: The tank has never been used, in absolute new condition, New agitator.; we can't give any guarantees about the agitator

Volumetric volume (L): 118 L

Ra inner weld: 0,80

Finish stainless steel: 2B

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 316L (V4A)

Model: vertical



Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Shape of tank: cylindrical

Bottom type: flat

Total discharge: yes

Fixation points: 3 adjustable feet

Fixation point(s): RVS 304L

Wet parts agitator(s): SS AISI 316L (V4A)

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Tank outlet: inside Ø 40 mm

Outlet type: DIN11851

Total outlet valve: no, optional

Agitator: yes

Agitator type: propeller agitator

Position engine: at the top

Number of revolutions: 1.400

Power: 0,75

Voltage: mono

Cylinder: 2 mm

Bottom: 2 mm

Internal diameter tank: 495 mm

Distance from outlet to ground: 260 mm

Outer diameter tank: 605 mm

Cylinder height: 615 mm

Total height of tank: 1.310 mm

Empty weight tank: 60

SKU: 84079

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Finish rostfritt stål: 2b

Konfiguration: single-skin

Mobil tank: Nej

Övrig information: The tank has never been used, in absolute new condition, New agitator.; we can't give any guarantees about the agitator

Omrörare: Ja

Ra innersvets: 0,80

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: flat

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316L (V4A)

Volym i liter: 118



Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 40 mm
Teknisk ritning finns: Nej
Utloppstyp: DIN11851

Översikt material

Material: Syrafast 316
Fixeringspunkt(er): RVS 304L
Material vätskeberörd del på omrörare: SS AISI 316L (V4A)

Dimensioner av tank

Cylinderhöjd: 615 mm
Invändig diameter: 495 mm
Mått utlopp till marken: 260 mm
Total höjd: 1.310 mm
Ytterdiameter: 605 mm

Omrörare

Kraft (kW): 0,75
Position motor: at the top
Typ av omrörare: propeller agitator
Varvtal: 1.400
Spänning (Volt): mono

Tjocklek på tank

Botten: 2 mm
Cylinder: 2 mm

Mer

Isolerad: Nej

Vikt: 60