

1260 liter tank i Syrafast 316



75,000,00 kr /st exkl moms

Additional information: chemistry; 1 strong dent in the insulation jacket; some residues of previous content

Volumetric volume (L): 1.260 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 4 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 106 L

Max Overpressure: 2,50 Bar

Max onderdruk: 1 Bar

Max. working temperature: 150 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: DN40 DIN 11851

Internal diameter tank: 1.080 mm

Outer diameter tank: 1.250 mm

Cylinder height: 1.100 mm

Total height of tank: 2.900 mm

SKU: 270790

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: chemistry; 1 strong dent in the insulation jacket; some residues of previous content; we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Övertryck: 4 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1260

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 1.100 mm
Invändig diameter: 1.080 mm
Total höjd: 2.900 mm
Ytterdiameter: 1.250 mm

Mer

Isolerad: Ja