

130 liter tank i Syrafast 316



43,000,00 kr /st exkl moms

Additional information: 2x Trolley available for tanks; some tanks with smaller dents

Volumetric volume (L): 130 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: no

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Outlet of tank: non-existent

Cylinder: 2,50 mm

Bottom: 2,50 mm

Internal diameter tank: 508 mm

Cylinder height: 488 mm

Empty weight tank: 250

SKU: 391955

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: single-skin

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: 2x Trolley available for tanks; some tanks with smaller dents

Omrörare: Nej

Övertryck: 3 Bar

Total urtappning: Nej

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 130

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 488 mm

Invändig diameter: 508 mm

Tjocklek på tank

Botten: 2,50 mm

Cylinder: 2,50 mm

Mer

Isolerad: Nej

Vikt: 250