

## 150 liter tank i Syrafast 316



**87,000,00 kr /st exkl moms**

**Article type:** second-hand pressure tank

**Additional information:** The tank has never been used

**Capacity:** 150 L

**Maximal density of the product:** 1.400

**Ra inner weld:** 1,60

**Working pressure in tank:** vacuum

**Overpressure:** 6 Bar

**Underpressure (vacuum):** -1 Bar

**Max. working temperature:** 150 °C

**Min. working temperature:** -10 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** single-skin

**Heat exchanger:** no

**Insulation:** no

**Agitator:** no

**Mobile tank:** no

**Top type:** flat

**Shape of tank:** cylindrical

**Bottom type:** dished

**Bottom outlet:** yes

**Total discharge:** yes

**Fixation points:** 3 non adjustable feet

**Gasket manway(s):** PTFE

**Fixation point(s):** RVS 304L

**Suitable for food industry:** yes

**Documents included:** no

**Technical drawing included:** yes

**Registration plate on the tank:** no

**Flange for agitator:** no

**Number of manways:** 1

**Position manway:** at the top

**Manway 1:** 461 mm

**Tank outlet:** inside Ø 76 mm

**Outlet type:** DN65 EN1092-1

**Top:** 36 mm

**Cylinder:** 3 mm

**Bottom:** 4 mm

**Tank capacity top cylinder:** 150 L

**Internal diameter tank:** 461,60 mm

**Distance from outlet to ground:** 250 mm

**Outer diameter tank:** 615 mm

**Cylinder height:** 856 mm

**Total height of tank:** 1.414 mm

**SKU:** 187437

## Mer information

### Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Omrörare: Nej

Trycktank: Ja

Volym i liter: 150

### Utrustning

Livsmedelsklassad: Ja

### Översikt material

Material: Syrafast 316

### Dimensioner av tank

Cylinderhöjd: 856 mm

Ytterdiameter: 615 mm