

## 1500 liter tank i Rostfritt 304



**113,000,00 kr /st exkl moms**

**Article type:** second-hand pressure tank

**Additional information:** The lid for the smaller connection on the top is missing, the cap for the electromotor is missing, the nuts for the manway are missing; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

**Volumetric volume (L):** 1.500 L

**Ra inner weld:** 0,80

**Pressure in tank:** pressure

**Design pressure (Bar):** 5,25 Bar

**Max. pressure (Bar):** 3 Bar

**Min. pressure (Bar):** -1 Bar  
**Max. temperature (°C):** 135 °C  
**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical  
**Configuration:** insulated with heat-exchanger  
**Heat exchanger:** yes  
**Insulation:** yes  
**Mobile tank:** no

**Top type:** dished  
**Shape of tank:** cylindrical  
**Bottom type:** dished  
**Total discharge:** yes  
**Fixation points:** 3 non adjustable feet

**Water pressure HE:** 5 Bar  
**Hydraulic test pressure:** 6,89 Bar  
**Working temperature HE cylinder:** 135 °C  
**Manway(s):** RVS 304  
**Gasket manway(s):** unknown

**Valve:** RVS 304  
**Gasket shut-off valve (mat):** unknown  
**Fixation point(s):** RVS 304  
**Wet parts agitator(s):** SS AISI 304 (V2A)  
**Suitable for food industry:** yes

**Documents included:** no  
**Technical drawing included:** no  
**Registration plate on the tank:** no  
**Flange for agitator:** no  
**Number of manways:** 1

**Position of manway:** at the top  
**Total outlet valve:** yes  
**Agitator:** yes  
**Agitator type:** tripod  
**Position engine:** in the bottom

**Outer diameter tank:** 1.500 mm

**Total height of tank:** 2.000 mm

**Empty weight tank:** 750

**SKU:** 20070

---

Mer information

## Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure

Designtryck för tanken: 5,25 Bar

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 135 °C

Mobil tank: Nej

Övrig information: The lid for the smaller connection on the top is missing, the cap for the electromotor is missing, the nuts for the manway are missing; we can't give any guarantees about the heating/cooling jacket;

Övrig information2: we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3 Bar

Ra innersvets: 0,80

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: dished

Undertryck (vakuum): -1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 1500

## Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Livsmedelsklassad: Ja

Teknisk ritning finns: Nej

Utloppsventil: Ja

## Översikt material

Material: Rostfritt 304

Fixeringspunkt(er): RVS 304

Material vätskeberörd del på omrörare: SS AISI 304 (V2A)

## Dimensioner av tank

Total höjd: 2.000 mm

Ytterdiameter: 1.500 mm

## Värmeväxlare

Arbetstemperatur värmeväxlare cylinder: 135 °C

Hydrauliskt provtryck botten: 6,89 Bar

Hydrauliskt provtryck: 6,89 Bar

Vattentryck värmeväxlare: 5 Bar

## Omrörare

Position motor: in the bottom

Typ av omrörare: tripad

## Mer

Isolerad: Ja

Vikt: 750