

15000 liter tank i Syrafast 316



525,000,00 kr /st exkl moms

Additional information: Total height as per drawing

Volumetric volume (L): 15.000 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 90 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 48 L

Max Overpressure: 3 Bar

Max. working temperature: 90 °C

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: yes

Position of manway: in the bottom

Outlet of tank: 76

Internal diameter tank: 2.300 mm

Outer diameter tank: 2.450 mm

Cylinder height: 3.750 mm

Total height of tank: 5.610 mm

SKU: 441299

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 90 °C

Mobil tank: Nej

Övrig information: Total height as per drawing; we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 15000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Ja

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 3.750 mm
Invändig diameter: 2.300 mm
Total höjd: 5.610 mm
Ytterdiameter: 2.450 mm

Mer

Isolerad: Ja