

## 16150 liter tank i Syrafast 316



## 254,000,00 kr /st exkl moms

**Additional information:** Dairy; Double jacket with trickle ring - only suitable for pressureless cooling; In some places the welding of the double jackets in the upper area has come loose slightly

**Volumetric volume (L):** 16.150 L

**Pressure in tank:** pressure

**Max. pressure (Bar):** 3,20 Bar

**Max. temperature (°C):** 150 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** single jacketed with heat-exchanger

**Heat exchanger:** yes

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 1.000 L

**Max Overpressure:** 3,20 Bar

**Max. working temperature:** 150 °C

**Type HE on the bottom:** heating/cooling jacket

**Type HE on the cylinder:** heating/cooling jacket

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** in the bottom

**Outlet of tank:** 80

**Agitator:** yes

**Number of revolutions:** 720 / 1460

**Power:** 1.7 / 6.8

**Cylinder:** 8 mm

**Bottom:** 6 mm

**Internal diameter tank:** 2.490 mm

**Outer diameter tank:** 2.580 mm

**Cylinder height:** 2.500 mm

**Total height of tank:** 5.000 mm

**SKU:** 435479

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Dairy; Double jacket with trickle ring – only suitable for pressureless cooling; in 1 tank the welding of the double jacket in the upper area has come loose in places; we can't give any guarantees

Övrig information2: about the agitator

Omrörare: Nej

Övertryck: 3.20 Bar

Total urtappning: Ja

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 16150

## Utrustning

Dokument finns: Nej  
Fläns för omrörare: Nej  
Märkskylt: Nej  
Teknisk ritning finns: Nej

## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 2.500 mm  
Invändig diameter: 2.490 mm  
Total höjd: 5.000 mm  
Ytterdiameter: 2.580 mm

## Omrörare

Kraft (kW): 1.7 / 6.8  
Varvtal: 720 / 1460

## Tjocklek på tank

Botten: 6 mm  
Cylinder: 8 mm

## Mer

Isolerad: Nej