

## 1660 liter tank i Syrafast 316



**184,000,00 kr /st exkl moms**

**Additional information:** Liquid soap; System drawing available; tank is the larger, left tank in the photo of the previous operator; tank was part of a process plant (the smaller tank in the photo is also available under order number 9787 (subject to sale elsewhere))

**Volumetric volume (L):** 1.660 L

**Pressure in tank:** ATM - atmosferic  
**Max. temperature (°C):** 150 °C  
**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical  
**Configuration:** insulated with heat-exchanger  
**Heat exchanger:** yes  
**Insulation:** yes  
**Mobile tank:** no

**Total discharge:** yes  
**Volume:** 165 L  
**Max Overpressure:** 6 Bar  
**Max. working temperature:** 150 °C  
**Type HE on the bottom:** heating/cooling jacket

**Type HE on the cylinder:** heating/cooling jacket  
**Documents included:** no  
**Technical drawing included:** no  
**Registration plate on the tank:** yes  
**Flange for agitator:** no

**Outlet of tank:** 100  
**Agitator:** yes  
**Number of revolutions:** 8,2 - 26,5  
**Power:** 7,50  
**Cylinder:** 10 mm

**Bottom:** 8 mm  
**Internal diameter tank:** 1.180 mm  
**Outer diameter tank:** 1.360 mm  
**Cylinder height:** 1.390 mm  
**Total height of tank:** 3.200 mm

**SKU:** 479118

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosfäric

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Liquid soap; System drawing available; 2 pumps are included in delivery (see photos); tank is the larger, left tank in the photo of the previous operator; tank was part of a process plant (the

Övrig information2: order number 9787 (subject to sale elsewhere); we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1660

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316



## Dimensioner av tank

Cylinderhöjd: 1.390 mm  
Invändig diameter: 1.180 mm  
Total höjd: 3.200 mm  
Ytterdiameter: 1.360 mm

## Omrörare

Kraft (kW): 7,50  
Varvtal: 8,2 - 26,5

## Tjocklek på tank

Botten: 8 mm  
Cylinder: 10 mm

## Mer

Isolerad: Ja