

## 1700 liter tank i Rostfritt 304



**74,000,00 kr /st exkl moms**

**Additional information:** Food industry; Operating pressure in the double jacket: 2.8 bar; 2 former connections in the upper bottom were welded shut by the previous operator

**Volumetric volume (L):** 1.700 L

**Pressure in tank:** ATM - atmosferic

**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical

**Configuration:** single jacketed with heat-exchanger

**Heat exchanger:** yes

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 210 L

**Max Overpressure:** 2,50 Bar

**Max. working temperature:** 150 °C

**Type HE on the bottom:** heating/cooling jacket

**Type HE on the cylinder:** heating/cooling jacket

**Heat exchanger:** RVS 304

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** in the bottom

**Outlet of tank:** DN50 DIN 11851

**Agitator:** yes

**Number of revolutions:** 72

**Power:** 1,50

**Internal diameter tank:** 1.330 mm

**Outer diameter tank:** 1.420 mm

**Cylinder height:** 1.200 mm

**Total height of tank:** 3.300 mm

**SKU:** 304382

## Mer information

### Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: single jacketed with heat-exchanger

Mobil tank: Nej

Övrig information: Food industry; Operating pressure in the double jacket: 2.8 bar; 2 former connections in the upper bottom were welded shut by the previous operator; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 1700

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Rostfritt 304

### Dimensioner av tank

Cylinderhöjd: 1.200 mm

Invändig diameter: 1.330 mm

Total höjd: 3.300 mm

Ytterdiameter: 1.420 mm

**Omrörare**

Kraft (kW): 1,50

Varvtal: 72

**Mer**

Värmeväxlare: RVS 304

Isolerad: Nej