

185 liter tank i Syrafast 316



130,000,00 kr /st exkl moms

Article type: second-hand pressure tank

Additional information:

The tanks have never been used.

Volumetric volume (L): 185 L

Pressure in tank: pressure

Max. pressure (Bar): 6 Bar

Min. pressure (Bar): -1 Bar

Max. temperature (°C): 130 °C



Min. temperature (°C): -10 °C
Material wet parts: SS AISI 316L (V4A)
Model: vertical

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Top type: flat

Shape of tank: cylindrical
Bottom type: dished
Bottom outlet: yes
Total discharge: yes
Fixation points: 3 non adjustable feet

Gasket manway(s): PTFE
Fixation point(s): RVS 316
Suitable for food industry: no
Documents included: yes, optional
Technical drawing included: yes

Registration plate on the tank: yes
Flange for agitator: no
Number of manways: 1
Position of manway: at the top
Tank outlet: outside Ø 65 mm

Agitator: no
Top: 38 mm
Cylinder: 4 mm
Bottom: 4 mm
Internal diameter tank: 502 mm

Distance from outlet to ground: 250 mm
Outer diameter tank: 670 mm
Total height of tank: 1.440 mm
Total outer width: 755,50 mm
Total outer length: 751,50 mm

Empty weight tank: 200

SKU: 439217

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure

Konfiguration: single-skin

Max. arbetstemperatur: 130 °C

Min. arbetstemperatur: -10 °C

Mobil tank: Nej

Övrig information: The tanks have never been used.

Omrörare: Nej

Övertryck: 6 Bar

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: dished

Undertryck (vakuum): -1 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316L (V4A)

Volym i liter: 185



Utrustning

Fläns för omrörare: Nej
Märkskylt: Ja
Tankutlopp: outside Ø 65 mm
Teknisk ritning finns: Ja

Översikt material

Material: Syrafast 316
Fixeringspunkt(er): RVS 316

Dimensioner av tank

Invändig diameter: 502 mm
Mått utlopp till marken: 250 mm
Total höjd: 1.440 mm
Ytterdiameter: 670 mm

Tjocklek på tank

Botten: 4 mm
Cylinder: 4 mm
Topp: 38 mm

Mer

Isolerad: Nej
Vikt: 200