

## 250 liter tank i Rostfritt 304



**52,000,00 kr /st exkl moms**

**Article type:** second-hand pressure tank

**Additional information:** Top lid is missing, a new lid = 650 €.

There are two connections provided with 2 inch internal thread for mounting 2 immersion resistors with an insertion length of 500mm, the immersion resistors themselves are not included.

**Volumetric volume (L):** 250 L

**Pressure in tank:** pressure

**Design pressure (Bar):** 5,20 Bar

**Max. pressure (Bar):** 3,50 Bar

**Max. temperature (°C):** 100 °C

**Material wet parts:** SS AISI 304L (V2A)

**Model:** vertical

**Configuration:** single jacketed with heat-exchanger

**Heat exchanger:** yes

**Insulation:** no

**Mobile tank:** no

**Top type:** dished

**Shape of tank:** cylindrical

**Bottom type:** dished

**Total discharge:** yes

**Fixation points:** on skirt

**Type of HE on the cylinder:** atmosfertical double jacket

**Type of HE on the bottom:** atmosfertical double jacket

**Heat exchanger:** RVS 304

**Fixation point(s):** RVS 304

**Suitable for food industry:** no

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Number of manways:** 1

**Position of manway:** at the top

**Height manhole 1 (mm):** 355 mm

**Tank outlet:** inside Ø 32 mm

**Outlet type:** bsp female

**Agitator:** no, optional

**Internal diameter tank:** 695 mm

**Distance from outlet to ground:** 400 mm

**Outer diameter tank:** 795 mm

**Cylinder height:** 560 mm

**Total height of tank:** 1.370 mm

**Empty weight tank:** 300

SKU: 61114

## Mer information

### Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure

Designtryck för tanken: 5,20 Bar

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 100 °C

Mobil tank: Nej

Övrig information: Top lid is missing, a new lid = 650 €. There are two connections provided with 2 inch internal thread for mounting 2 immersion resistors with an insertion length of 500mm, the immersion

Övrig information2: resistors themselves are not included.

Omrörare: Nej

Övertryck: 3.50 Bar

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: dished

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304L (V2A)

Volym i liter: 250



## Utrustning

Dokument finns: Nej  
Fläns för omrörare: Nej  
Märkskylt: Ja  
Tankutlopp: inside Ø 32 mm  
Teknisk ritning finns: Nej  
Utloppstyp: bsp female

## Översikt material

Material: Rostfritt 304  
Fixeringspunkt(er): RVS 304

## Dimensioner av tank

Cylinderhöjd: 560 mm  
Invändig diameter: 695 mm  
Mått utlopp till marken: 400 mm  
Total höjd: 1.370 mm  
Ytterdiameter: 795 mm

## Värmeväxlare

Typ av värmeväxlare på cylinder: atmosfertical double jacket  
Typ av värmeväxlare på botten: atmosfertical double jacket

## Mer

Värmeväxlare: RVS 304  
Isolerad: Nej  
Vikt: 300