

2500 liter tank i Syrafast 316



198,000,00 kr /st exkl moms

Additional information: Chemistry; Support ring made of Fe; smaller dents in the insulation jacket; Manhole cover partially plated; diameter manhole 490 mm; some residues of previous content

Volumetric volume (L): 2.500 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3,20 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 180 L

Max Overpressure: 16 Bar

Max onderdruk: 1 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: 130

Agitator: yes

Number of revolutions: 307

Power: 1,10

Internal diameter tank: 1.590 mm

Outer diameter tank: 1.880 mm

Cylinder height: 1.380 mm

Total height of tank: 3.250 mm

SKU: 273763

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Chemistry; Support ring made of Fe; smaller dents in the insulation jacket; Manhole cover partially plated; diameter manhole 490 mm; some residues of previous content; we can't give any guarantees

Övrig information2: about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3.20 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 2500

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.380 mm

Invändig diameter: 1.590 mm

Total höjd: 3.250 mm

Ytterdiameter: 1.880 mm

Omrörare

Kraft (kW): 1,10

Varvtal: 307

Mer

Isolerad: Ja