

## 2765 liter tank i Syrafast 316



**86,000,00 kr /st exkl moms**

**Additional information:** Chemistry; Tanks blasted and primed on the outside; Double jacket screwed to the lower bottom (see photos); 4 support brackets made of Fe; external surface damaged in places (possibly in need of repair); some residues of previous content

**Volumetric volume (L):** 2.765 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 6 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 200 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** single jacketed with heat-exchanger

**Heat exchanger:** yes

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 42 L

**Max Overpressure:** 3 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 150 °C

**Type HE on the bottom:** heating/cooling jacket

**Heat exchanger:** RVS 304

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Outlet of tank:** flange DN80

**Agitator:** yes

**Number of revolutions:** 167

**Power:** 2,60

**Top:** 9 mm

**Cylinder:** 7 mm

**Bottom:** 7 mm

**Internal diameter tank:** 1.400 mm

**Cylinder height:** 1.390 mm

**Total height of tank:** 3.350 mm

**SKU:** 273685

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Chemistry; Tanks blasted and primed on the outside; Double jacket screwed to the lower bottom (see photos); 4 support brackets made of Fe; external surface damaged in places (possibly in need of

Övrig information2: repair); some residues of previous content; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 6 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 2765

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej



## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 1.390 mm

Invändig diameter: 1.400 mm

Total höjd: 3.350 mm

## Omrörare

Kraft (kW): 2,60

Varvtal: 167

## Tjocklek på tank

Botten: 7 mm

Cylinder: 7 mm

Topp: 9 mm

## Mer

Värmeväxlare: RVS 304

Isolerad: Nej