

## 285 liter tank i Syrafast 316



**67,000,00 kr /st exkl moms**

**Additional information:** Food industry; 1 longitudinal sight glass in the cylinder; slight metallic discoloration inside the tanks; the stated total height refers to 1 of the 2 tanks, which also has a screwed-in foot elevation (see photo; the second tank is approx. 100 mm lower); the higher tank with an outlet DN 50 DIN 11851 (the lower tank with a screwed-on fitting DN 20 DIN 11851)

**Volumetric volume (L):** 285 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 6 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 200 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** single jacketed with heat-exchanger

**Heat exchanger:** yes

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 46 L

**Max Overpressure:** 6 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 200 °C

**Type HE on the bottom:** heating/cooling jacket

**Type HE on the cylinder:** heating/cooling jacket

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Outlet of tank:** available

**Top:** 5 mm

**Cylinder:** 6 mm

**Bottom:** 6 mm

**Internal diameter tank:** 640 mm

**Outer diameter tank:** 690 mm

**Cylinder height:** 770 mm

**Total height of tank:** 2.020 mm

**SKU:** 305042

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Food industry; 1 longitudinal sight glass in the cylinder; slight metallic discoloration inside the tanks; the stated total height refers to 1 of the 2 tanks, which also has a screwed-in foot

Övrig information2: elevation (see photo; the second tank is approx. 100 mm lower); the higher tank with an outlet DN 50 DIN 11851 (the lower tank with a screwed-on fitting DN 20 DIN 11851)

Omrörare: Nej

Övertryck: 6 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 285

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej



## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 770 mm

Invändig diameter: 640 mm

Total höjd: 2.020 mm

Ytterdiameter: 690 mm

## Tjocklek på tank

Botten: 6 mm

Cylinder: 6 mm

Topp: 5 mm

## Mer

Isolerad: Nej