

3000 liter tank i Syrafast 316



256,000,00 kr /st exkl moms

Additional information: Dairy; 1 manhole approx. 420 x 535 mm in the front bottom, 1 side handhole diameter approx. 200 mm; covers in the rear area are missing (see photos), tank is equipped with 2 conveyor screws (technical data can be found in the "Agitator" section)

Volumetric volume (L): 3.000 L

Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 316 (V4A)
Configuration: single-skin

Heat exchanger: no
Insulation: no
Mobile tank: no
Total discharge: no
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Number of revolutions: 8,40
Power: 2,20

Total height of tank: 2.350 mm
Total outer width: 1.250 mm
Total outer length: 3.050 mm

SKU: 440990

Mer information

Beskrivning av produkt

Material: Syrafast 316

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Mobil tank: Nej

Övrig information: Dairy; 1 manhole approx. 420 x 535 mm in the front bottom, 1 side handhole diameter approx. 200 mm; covers in the rear area are missing (see photos), tank is equipped with 2 conveyor screws

Övrig information2: (technical data can be found in the "Agitator" section)

Omrörare: Nej

Total urtappning: Nej

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 3000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Total höjd: 2.350 mm

Omrörare

Kraft (kW): 2,20

Varvtal: 8,40

Mer

Isolerad: Nej
