

30000 liter tank i Rostfritt 304



153,000,00 kr /st exkl moms

Article type: second-hand storage tank

Additional information: Stainless steel tank with steel painted outer jacket. The outer jacket is insulated with 150mm PIR and clad with screwed stainless steel plates.

Volumetric volume (L): 30.000 L

Ra inner weld: 0,80

Finish stainless steel: 2B

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: horizontal



Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Shape of tank: cylindrical

Wall type: conical

Total discharge: yes

Fixation points: 6 non adjustable feet

Insulation material: PIR

Outer jacket (ornamental wall): RVS 304

Manway(s): RVS 304

Gasket manway(s): unknown

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: headside

Height manhole 1 (mm): 500 mm x H 390 mm

Tank outlet: inside Ø 70 mm

Agitator: no, optional

finish of the outer jacket: riveted

Insulation thickness: 150

Internal diameter tank: 2.880 mm

Distance from outlet to ground: 200 mm

Outer diameter tank: 3.200 mm

Cylinder height: 4.450 mm

Total height of tank: 3.500 mm

Total outer length: 5.800 mm

Empty weight tank: 4.000

SKU: 189089

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Horisontell

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Finish rostfritt stål: 2b

Konfiguration: insulated

Mobil tank: Nej

Övrig information: Stainless steel tank with steel painted outer jacket. The outer jacket is insulated with 150mm PIR and clad with screwed stainless steel plates.

Omrörare: Nej

Ra innersvets: 0,80

Tankens form: cylindrical

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 30000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Livsmedelsklassad: Ja

Tankutlopp: inside Ø 70 mm

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Isoleringsmaterial: PIR

Ytterbeklädnad: RVS 304

Dimensioner av tank

Cylinderhöjd: 4.450 mm

Invändig diameter: 2.880 mm

Mått utlopp till marken: 200 mm

Total höjd: 3.500 mm

Ytterdiameter: 3.200 mm

Tjocklek på ytterbeklädnad och isolering

Finish utvändig mantel: riveted

Isoleringsmaterial: PIR

Mer

Isoleringstjocklek: 150

Isoleringstjocklek OW: 150

Isolerad: Ja

Vikt: 4.000