

324 liter tank i Syrafast 316



39,000,00 kr /st exkl moms

Additional information: Tank hanging on 3 "feet" in frame or ceiling; Hand hole diameter approx. 300 mm; Outlet fitting is missing; some residues of previous content

Volumetric volume (L): 324 L

Pressure in tank: ATM - atmospheric

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 134 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: no

Max Overpressure: 3 Bar

Max onderdruk: 1 Bar

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: DN40 DIN 11851

Number of revolutions: 940 / 435

Power: 0.55 / 0.12

Internal diameter tank: 800 mm

Cylinder height: 430 mm

Total height of tank: 1.650 mm

SKU: 278632

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: single-skin

Max. arbetstemperatur: 134 °C

Mobil tank: Nej

Övrig information: Tank hanging on 3 "feet" in frame or ceiling; Hand hole diameter approx. 300 mm; Outlet fitting is missing; some residues of previous content

Omrörare: Ja

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 324

Utrustning

Dokument finns: Nej

Fläns för omrörare: Ja

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 430 mm

Invändig diameter: 800 mm

Total höjd: 1.650 mm



Omrörare

Kraft (kW): 0.55 / 0.12

Varvtal: 940.435

Mer

Isolerad: Nej