

## 3500 liter tank i Syrafast 316



**115,000,00 kr /st exkl moms**

**Additional information:** rennet-production; Feet originally stood on load cells, these are no longer available (see pictures); according to the type plate, the heating coil is designed for an operating pressure of 3 bar at a temperature of - 5 ° C (see photos on the type plate); diameter manhole 430 mm; suspension of manhole cover incomplete

**Volumetric volume (L):** 3.500 L

**Pressure in tank:** ATM - atmosferic

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 62 L

**Max Overpressure:** 3 Bar

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Heat exchanger:** RVS 304

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** in the bottom

**Outlet of tank:** DN40 DIN 11851

**Agitator:** yes

**Number of revolutions:** 910

**Power:** 0,55

**Internal diameter tank:** 1.350 mm

**Outer diameter tank:** 1.560 mm

**Cylinder height:** 2.500 mm

**Total height of tank:** 3.450 mm

**SKU:** 270919

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Mobil tank: Nej

Övrig information: rennet-production; Feet originally stood on load cells, these are no longer available (see pictures); according to the type plate, the heating coil is designed for an operating pressure of 3 bar at

Övrig information2:

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 3500

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316



## Dimensioner av tank

Cylinderhöjd: 2.500 mm  
Invändig diameter: 1.350 mm  
Total höjd: 3.450 mm  
Ytterdiameter: 1.560 mm

## Omrörare

Kraft (kW): 0,55  
Varvtal: 910

## Mer

Värmeväxlare: RVS 304  
Isolerad: Ja