

## 3532 liter tank i Syrafast 316



**179,000,00 kr /st exkl moms**

**Additional information:** Pharmaceutical Chemistry; 3 support brackets made of Fe; half-coil around the lower cylinder area; 1 heating connection probably slightly bent; bump at the insulation jacket; manhole cover plated

**Volumetric volume (L):** 3.532 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 3,20 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 100 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 103 L

**Max Overpressure:** 16 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 100 °C

**Type HE on the bottom:** half pipe welded onto the outside of the innertank

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Heat exchanger:** RVS 304

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** in the bottom

**Outlet of tank:** available

**Agitator:** yes

**Number of revolutions:** 313

**Power:** 1,10

**Internal diameter tank:** 1.590 mm

**Outer diameter tank:** 1.800 mm

**Total height of tank:** 3.300 mm

**Empty weight tank:** 1.450

**SKU:** 273976

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 100 °C

Mobil tank: Nej

Övrig information: Pharmaceutical Chemistry; 3 support brackets made of Fe; half-coil around the lower cylinder area; 1 heating connection probably slightly bent ; bump at the insulation jacket;manhole cover plated;

Övrig information2: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3.20 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 3532

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej



## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Invändig diameter: 1.590 mm

Total höjd: 3.300 mm

Ytterdiameter: 1.800 mm

## Omrörare

Kraft (kW): 1,10

Varvtal: 313

## Mer

Värmeväxlare: RVS 304

Isolerad: Ja

Vikt: 1.450