

41300 liter tank i Syrafast 316



309,000,00 kr /st exkl moms

Additional information: Solvents; Cylinder manhole diameter: approx. 600 mm

Volumetric volume (L): 41.300 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 1 Bar

Min. pressure (Bar): 0,25 Bar

Max. temperature (°C): 100 °C

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: DN100 DIN 11851

Top: 8 mm

Cylinder: 6 mm

Bottom: 8 mm

Internal diameter tank: 3.200 mm

Cylinder height: 4.370 mm

Total height of tank: 7.230 mm

SKU: 475819

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single-skin

Max. arbetstemperatur: 100 °C

Mobil tank: Nej

Övrig information: Solvents; Cylinder manhole diameter: approx. 600 mm

Omrörare: Nej

Övertryck: 1 Bar

Total urtappning: Ja

Undertryck (vakuum): 0,25 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Volym i liter: 41300

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 4.370 mm

Invändig diameter: 3.200 mm

Total höjd: 7.230 mm

Tjocklek på tank

Botten: 8 mm

Cylinder: 6 mm

Topp: 8 mm

Mer

Isolerad: Nej