

## 42000 liter tank i GAP/Plast



**161,000,00 kr /st exkl moms**

item available on order

**Article type:** brand new storage tank - type MP-SEF

**Additional information:** lid for manway in stainless-steel (SS); set of anchorage points in stainless-steel (SS) included; tank will be delivered with Food grade certificate

**Volumetric volume (L):** 42.000 L

**Max. density P (kg/m<sup>3</sup>):** 1.300

**Pressure in tank:** ATM - atmosferic

**Max. temperature (°C):** 60 °C

**Min. temperature (°C):** -10 °C

**Material wet parts:** polyester (fiberglass)

**Model:** vertical

**Configuration:** single-skin

**Heat exchanger:** no

**Insulation:** no

**Mobile tank:** no

**Top type:** dished

**Shape of tank:** cylindrical

**Bottom type:** flat

**Total discharge:** no

**Fixation points:** Tighten the FIXATIONS only by hand !

**Outer jacket (ornamental wall):** polyester

**Manway(s):** RVS 316

**Fixation point(s):** RVS 304

**Suitable for food industry:** yes

**Documents included:** yes, optional

**Technical drawing included:** yes

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Number of manways:** 1

**Position of manway:** cylinder

**Height manhole 1 (mm):** 320 mm x H 435 mm

**Tank outlet:** inside Ø 50 mm

**Outlet type:** Guillement 2"

**Total outlet valve:** yes

**Outer diameter tank:** 3.000 mm

**Total height of tank:** 6.490 mm

**Empty weight tank:** 935

**SKU:** 5669

## Mer information

### Beskrivning av produkt

Livsmedelsklassad: Ja

Material: GAP/Plast

Modell: Vertikal

Nyttillverkad/Begagnad: Nyttillverkad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Max. arbetstemperatur: 60 °C

Maximal densitet för produkten: 1300

Min. arbetstemperatur: -10 °C

Mobil tank: Nej

Övrig information: lid for manway in stainless-steel (SS); set of anchorage points in stainless-steel (SS) included; tank will be delivered with Food grade certificate

Omrörare: Nej

Tankens form: cylindrical

Total urtappning: Nej

Typ av botten: flat

Uppvärmning/kylning: Nej

Vätskeberörd yta: polyester (fiberglass)

Volym i liter: 42000

### Utrustning

Fläns för omrörare: Nej

Märkskylt: Ja

Livsmedelsklassad: Ja

Tankutlopp: inside Ø 50 mm

Teknisk ritning finns: Ja

Utloppstyp: Guillemeent 2"

Utloppsventil: Ja



## Översikt material

Material: GAP/Plast

Fixeringspunkt(er): RVS 304

Ytterbeklädnad: polyester

## Dimensioner av tank

Total höjd: 6.490 mm

Ytterdiameter: 3.000 mm

## Mer

Isolerad: Nej

Vikt: 935