

500 liter tank i Syrafast 316



58,000,00 kr /st exkl moms

Additional information: Pharmaceutical Chemistry; 4 support Brackets, st. st.; 1 manhole diameter approx. 350 mm in the front bottom; smaller dents in the insulating jacket

Volumetric volume (L): 500 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 6 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: flange DN50

Internal diameter tank: 690 mm

Outer diameter tank: 800 mm

Total outer length: 1.650 mm

SKU: 298360

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Pharmaceutical Chemistry; 4 support Brackets, st. st.; 1 manhole diameter approx. 350 mm in the front bottom; smaller dents in the insulating jacket

Omrörare: Nej

Övertryck: 6 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 500

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Invändig diameter: 690 mm

Ytterdiameter: 800 mm

Mer

Isolerad: Ja
