

5000 liter tank i Rostfritt 304



219,000,00 kr /st exkl moms

Additional information: Food industry; Heating coil outside around the lower cylinder area; 3 of the feet are equipped with load cells (no guarantee of functionality); one foot is missing the load cell; some residues of previous content

Volumetric volume (L): 5.000 L

Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: insulated with heat-exchanger
Heat exchanger: yes
Insulation: yes
Mobile tank: no
Total discharge: yes

Volume: 102 L
Max Overpressure: 4 Bar
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: in the bottom
Outlet of tank: 48
Agitator: yes

Internal diameter tank: 1.600 mm
Outer diameter tank: 1.870 mm
Cylinder height: 2.150 mm
Total height of tank: 4.100 mm

SKU: 456050

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Mobil tank: Nej

Övrig information: Food industry; Heating coil outside around the lower cylinder area; 3 of the feet are equipped with load cells (no guarantee of functionality); one foot is missing the load cell ; some residues of

Övrig information2: previous content; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 5000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 2.150 mm

Invändig diameter: 1.600 mm

Total höjd: 4.100 mm

Ytterdiameter: 1.870 mm

Mer

Isolerad: Ja
