

## 5000 liter tank i Rostfritt 304



**45,000,00 kr /st exkl moms**

**Additional information:** dairy; dents in the inner cylinder (overpressure double jacket); insulation jacket partly sliced and new tack welded; bump at the insulation jacket

**Volumetric volume (L):** 5.000 L

**Pressure in tank:** ATM - atmosferic

**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical

**Configuration:** insulated

**Heat exchanger:** no

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** in the bottom

**Outlet of tank:** flange DN65

**Agitator:** yes

**Power:** 0.5 / 0.75

**Internal diameter tank:** 2.000 mm

**Outer diameter tank:** 2.150 mm

**Cylinder height:** 1.500 mm

**Total height of tank:** 3.000 mm

**Empty weight tank:** 860

**SKU:** 268801

Mer information

## Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: insulated

Mobil tank: Nej

Övrig information: dairy; dents in the inner cylinder (overpressure double jacket); insulation jacket partly sliced and new tack welded; bump at the insulation jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 5000

## Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

## Översikt material

Material: Rostfritt 304

## Dimensioner av tank

Cylinderhöjd: 1.500 mm

Invändig diameter: 2.000 mm

Total höjd: 3.000 mm

Ytterdiameter: 2.150 mm

## Omrörare

Kraft (kW): 0.5 / 0.75

**Mer**

Isolerad: Ja

Vikt: 860

---