

530 liter tank i Syrafast 316



176,000,00 kr /st exkl moms

Additional information: Pharmacy; Original drawing available; tank was rebuilt in 1997 (e.g. changing the feet or connections); Evidence of the subsequent pressure test available; Conversion drawing only available as a fax; 1 dip tube inside the tank; some residues of previous content

Volumetric volume (L): 530 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 143 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 70 L

Max Overpressure: 3 Bar

Max onderdruk: 1 Bar

Max. working temperature: 143 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: DN80 DIN 11851

Agitator: yes

Number of revolutions: 670

Power: 0,55

Cylinder: 5 mm

Bottom: 5 mm

Internal diameter tank: 800 mm

Outer diameter tank: 900 mm

Cylinder height: 900 mm

Total height of tank: 2.250 mm

SKU: 313667

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 143 °C

Mobil tank: Nej

Övrig information: Pharmacy; Original drawing available; tank was rebuilt in 1997 (e.g. changing the feet or connections); Evidence of the subsequent pressure test available; Conversion drawing only available as a

Övrig information2: fax; 1 dip tube inside the tank; some residues of previous content; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 530



Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 900 mm
Invändig diameter: 800 mm
Total höjd: 2.250 mm
Ytterdiameter: 900 mm

Omrörare

Kraft (kW): 0,55
Varvtal: 670

Tjocklek på tank

Botten: 5 mm
Cylinder: 5 mm

Mer

Isolerad: Ja