

## 5500 liter tank i Syrafast 316



**296,000,00 kr /st exkl moms**

**Additional information:** Saline solution; Dents in the insulation jacket possible; The production and documentation drawings are available from the manufacturer and can be purchased separately from there; some residues of previous content; pipe end cut flush

**Volumetric volume (L):** 5.500 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 2,50 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 140 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 154 L

**Max Overpressure:** 2,50 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 140 °C

**Type HE on the bottom:** heating/cooling jacket

**Type HE on the cylinder:** heating/cooling jacket

**Heat exchanger:** RVS 304

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** in the bottom

**Outlet of tank:** 38

**Agitator:** yes

**Number of revolutions:** 429

**Power:** 2,20

**Internal diameter tank:** 1.680 mm

**Outer diameter tank:** 1.890 mm

**Total height of tank:** 3.500 mm

**SKU:** 278833

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 140 °C

Mobil tank: Nej

Övrig information: Saline solution; Dents in the insulation jacket possible; The production and documentation drawings are available from the manufacturer and can be purchased separately from there ; some residues of

Övrig information2: previous content; pipe end cut flush; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 2.50 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 5500

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej



## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Invändig diameter: 1.680 mm

Total höjd: 3.500 mm

Ytterdiameter: 1.890 mm

## Omrörare

Kraft (kW): 2,20

Varvtal: 429

## Mer

Värmeväxlare: RVS 304

Isolerad: Ja