

5530 liter tank i Rostfritt 304



166,000,00 kr /st exkl moms

Additional information: Dairy; Double jacket probably with trickle ring - only suitable for pressureless tempering; the welding of the double jacket in the upper area has come loose slightly in places; outlet diameter 65 mm (tapers towards the tank to approx. 50 mm); small dents inside the tank; heating connections cut off; pipe end cut flush

Volumetric volume (L): 5.530 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3,20 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 145 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Max Overpressure: 3,20 Bar

Max onderdruk: 1 Bar

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: available

Agitator: yes

Number of revolutions: 15.5 / 31

Power: 0.8 / 1.6

Internal diameter tank: 1.550 mm

Outer diameter tank: 1.660 mm

Cylinder height: 2.500 mm

Total height of tank: 4.350 mm

SKU: 443435

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 145 °C

Mobil tank: Nej

Övrig information: Dairy; Double jacket probably with trickle ring – only suitable for pressureless tempering; the welding of the double jacket in the upper area has come loose slightly in places; outlet diameter 65

Övrig information2: mm (tapers towards the tank to approx. 50 mm); small dents inside the tank; heating connections cut off; pipe end cut flush; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3.20 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 5530

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 2.500 mm

Invändig diameter: 1.550 mm

Total höjd: 4.350 mm

Ytterdiameter: 1.660 mm

Omrörare

Kraft (kW): 0.8 / 1.6

Varvtal: 15.5 / 31

Mer

Isolerad: Nej