

6000 liter tank i Rostfritt 304



97,000,00 kr /st exkl moms

Additional information: Dairy; Small dents in the insulating jacket; 1 small crack and 1 rust pore inside the tank (note from the previous operator); small welded patches (?) inside the tank (see photos); Functionality of the double jacket not checked

Volumetric volume (L): 6.000 L

Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: insulated with heat-exchanger
Heat exchanger: yes
Insulation: yes
Mobile tank: no
Total discharge: yes

Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes

Flange for agitator: no
Position of manway: in the bottom
Outlet of tank: DN50 DIN 11851
Agitator: yes
Power: 1,50

Internal diameter tank: 2.120 mm
Outer diameter tank: 2.270 mm
Cylinder height: 1.550 mm
Total height of tank: 3.450 mm

SKU: 297227

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Mobil tank: Nej

Övrig information: Dairy; Small dents in the insulating jacket; 1 small crack and 1 rust pore inside the tank (note from the previous operator); small welded patches (?) inside the tank (see photos); Functionality

Övrig information2: of the double jacket not checked; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 6000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 1.550 mm

Invändig diameter: 2.120 mm

Total höjd: 3.450 mm

Ytterdiameter: 2.270 mm

Omrörare

Kraft (kW): 1,50

Mer

Isolerad: Ja
