

## 6000 liter tank i Rostfritt 304



**97,000,00 kr /st exkl moms**

**Additional information:** Dairy; Small dents in the insulating jacket; 1 small crack and 1 rust pore inside the tank (note from the previous operator); small welded patches (?) inside the tank (see photos); Functionality of the double jacket not checked

**Volumetric volume (L):** 6.000 L

**Pressure in tank:** ATM - atmosferic  
**Material wet parts:** SS AISI 304 (V2A)  
**Model:** vertical

**Configuration:** insulated with heat-exchanger  
**Heat exchanger:** yes  
**Insulation:** yes  
**Mobile tank:** no  
**Total discharge:** yes

**Type HE on the bottom:** heating/cooling jacket  
**Type HE on the cylinder:** heating/cooling jacket  
**Documents included:** no  
**Technical drawing included:** no  
**Registration plate on the tank:** yes

**Flange for agitator:** no  
**Position of manway:** in the bottom  
**Outlet of tank:** DN50 DIN 11851  
**Agitator:** yes  
**Power:** 1,50

**Internal diameter tank:** 2.120 mm  
**Outer diameter tank:** 2.270 mm  
**Cylinder height:** 1.550 mm  
**Total height of tank:** 3.450 mm

**SKU:** 297227

Mer information

## Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Mobil tank: Nej

Övrig information: Dairy; Small dents in the insulating jacket; 1 small crack and 1 rust pore inside the tank (note from the previous operator); small welded patches (?) inside the tank (see photos); Functionality

Övrig information2: of the double jacket not checked; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 6000

## Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

## Översikt material

Material: Rostfritt 304

## Dimensioner av tank

Cylinderhöjd: 1.550 mm

Invändig diameter: 2.120 mm

Total höjd: 3.450 mm

Ytterdiameter: 2.270 mm

**Omrörare**

Kraft (kW): 1,50

**Mer**

Isolerad: Ja

---