

6000 liter tank i Syrafast 316



211,000,00 kr /st exkl moms

Additional information: Pharmacy; Manhole DN 600; Parts of the blanking plugs may be present

Volumetric volume (L): 6.000 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 135 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: cylinder

Outlet of tank: 187

Top: 5,80 mm

Cylinder: 6 mm

Bottom: 6 mm

Internal diameter tank: 2.000 mm

Cylinder height: 1.350 mm

Total height of tank: 2.630 mm

SKU: 283813

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single-skin

Max. arbetstemperatur: 135 °C

Mobil tank: Nej

Övrig information: Pharmacy; Manhole DN 600; Parts of the blanking plugs may be present

Omrörare: Nej

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 6000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.350 mm

Invändig diameter: 2.000 mm

Total höjd: 2.630 mm

Tjocklek på tank

Botten: 6 mm

Cylinder: 6 mm

Topp: 5,80 mm

Mer

Isolerad: Nej