

6000 liter tank i Syrafast 316



361,000,00 kr /st exkl moms

Additional information: Pharmacy; Manhole DN 600; Outlet with screwed fitting; No reference to the acceptance of the double jacket in the test report on the acceptance (in a copy of drawing 1160246-1A or 1B there is the signed stamp "Tested according to AD 2000 rules from TÜV Süd"); Parts of the blind screw connections may be present



Volumetric volume (L): 6.000 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 135 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 135 °C

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: cylinder

Outlet of tank: 187

Agitator: yes

Number of revolutions: 495

Top: 5,80 mm

Cylinder: 6 mm

Bottom: 6 mm

Internal diameter tank: 2.000 mm

Outer diameter tank: 2.100 mm

Cylinder height: 1.400 mm

Total height of tank: 2.630 mm

SKU: 461925

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 135 °C

Mobil tank: Nej

Övrig information: Pharmacy; Manhole DN 600; Outlet with screwed fitting; No reference to the acceptance of the double jacket in the test report on the acceptance (in a copy of drawing

1160246-1A or 1B there is the

Övrig information2: signed stamp "Tested according to AD 2000 rules from TÜV Süd); Parts of the blind screw connections may be present

Omrörare: Ja

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 6000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.400 mm

Invändig diameter: 2.000 mm

Total höjd: 2.630 mm

Ytterdiameter: 2.100 mm

Omrörare

Varvtal: 495

Tjocklek på tank

Botten: 6 mm

Cylinder: 6 mm

Topp: 5,80 mm

Mer

Isolerad: Ja