

60000 liter tank i Rostfritt 304



519,000,00 kr /st exkl moms

Additional information: Rapeseed oil; Manhole cylinder NW 600; smaller sheet metal cutouts in the insulation jacket; bump at the insulation jacket; manhole cover plated

Volumetric volume (L): 60.000 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 1,50 Bar

Min. pressure (Bar): 0,20 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 105 L

Max Overpressure: 6 Bar

Max onderdruk: 0,20 Bar

Max. working temperature: 250 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: flange DN80

Top: 7 mm

Cylinder: 5 mm

Bottom: 10 mm

Internal diameter tank: 3.000 mm

Outer diameter tank: 3.200 mm

Cylinder height: 9.000 mm

Total outer length: 12.300 mm

SKU: 294232

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: chemistry; we can't give any guarantees about the heating/cooling jacket

Övrig information2: heating/cooling jacket

Omrörare: Nej

Övertryck: 1.50 Bar

Total urtappning: Ja

Undertryck (vakuum): 0,20 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 60000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 9.000 mm

Invändig diameter: 3.000 mm

Ytterdiameter: 3.200 mm

Tjocklek på tank

Botten: 10 mm

Cylinder: 5 mm

Topp: 7 mm

Mer

Isolerad: Ja