

## 630 liter tank i Syrafast 316



**61,000,00 kr /st exkl moms**

**Additional information:** chemistry; support ring and vessel flange made of mild steel; handholecover cladded

**Volumetric volume (L):** 630 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 6 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 300 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** single jacketed with heat-exchanger

**Heat exchanger:** yes

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 15 L

**Max Overpressure:** 32 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 300 °C

**Type HE on the bottom:** half pipe welded onto the outside of the innertank

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Heat exchanger:** RVS 316

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Outlet of tank:** flange DN50

**Agitator:** yes

**Top:** 15,80 mm

**Cylinder:** 7,80 mm

**Bottom:** 15,30 mm

**Internal diameter tank:** 1.000 mm

**Cylinder height:** 800 mm

**Total height of tank:** 2.000 mm

**SKU:** 267046

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 300 °C

Mobil tank: Nej

Övrig information: chemistry; support ring and vessel flange made of mild steel; handholecover cladded; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 6 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 630

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316



## Dimensioner av tank

Cylinderhöjd: 800 mm

Invändig diameter: 1.000 mm

Total höjd: 2.000 mm

## Tjocklek på tank

Botten: 15,30 mm

Cylinder: 7,80 mm

Topp: 15,80 mm

## Mer

Värmeväxlare: RVS 316

Isolerad: Nej