

70000 liter tank i Rostfritt 304



781,000,00 kr /st exkl moms

Additional information: manhole in the cylinder diameter 600 mm; Complete manufacturer documentation available; A ladder also available upon request; tank has fixtures for field installation of insulation (this fixture is slightly dented); some residues of previous content

Volumetric volume (L): 70.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: no

Max Overpressure: 6 Bar

Max. working temperature: 120 °C

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Agitator: yes

Number of revolutions: 23

Power: 22

Top: 5 mm

Cylinder: 5 mm

Bottom: 6 mm

Internal diameter tank: 3.490 mm

Cylinder height: 8.250 mm

Total height of tank: 11.040 mm

Total outer width: 3.820 mm

Total outer length: 3.820 mm

SKU: 301614

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: single jacketed with heat-exchanger

Mobil tank: Nej

Övrig information: manhole in the cylinder diameter 600 mm; Complete manufacturer documentation available; A ladder also available upon request; tank has fixtures for field installation of insulation (this fixture is

Övrig information2: slightly dented); some residues of previous content; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Nej

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 70000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej



Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 8.250 mm

Invändig diameter: 3.490 mm

Total höjd: 11.040 mm

Omrörare

Kraft (kW): 22

Varvtal: 23

Tjocklek på tank

Botten: 6 mm

Cylinder: 5 mm

Topp: 5 mm

Mer

Isolerad: Nej