

720 liter tank i Syrafast 316



61,000,00 kr /st exkl moms

Additional information: chemistry; 3 support brackets Fe; screws of the upper bottom flange are mostly missing; motor-/gear is missing

Volumetric volume (L): 720 L

Pressure in tank: pressure

Max. pressure (Bar): 2 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 52 L

Max Overpressure: 6 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 316

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: available

Agitator: yes

Internal diameter tank: 790 mm

Cylinder height: 1.220 mm

Total height of tank: 2.250 mm

SKU: 267235

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: chemistry; 3 support brackets Fe; screws of the upper bottom flange are mostly missing; motor-/gear is missing; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 2 Bar

Total urtappning: Ja

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 720

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.220 mm

Invändig diameter: 790 mm

Total höjd: 2.250 mm

Mer

Värmeväxlare: RVS 316

Isolerad: Nej
