

8300 liter tank i Rostfritt 304



165,000,00 kr /st exkl moms

Additional information: Herbal pharmacy; Durchmesser Mannloch 510 mm; some residues of previous content; manhole cover is missing

Volumetric volume (L): 8.300 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 1,96 Bar

Min. pressure (Bar): 0,83 Bar

Max. temperature (°C): 50 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 770 L

Max Overpressure: 1,96 Bar

Max onderdruk: 0,83 Bar

Max. working temperature: 80 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: 53

Agitator: yes

Number of revolutions: 489

Power: 2,50

Internal diameter tank: 1.980 mm

Outer diameter tank: 2.250 mm

Cylinder height: 2.250 mm

Total height of tank: 4.500 mm

SKU: 312430

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 50 °C

Mobil tank: Nej

Övrig information: Herbal pharmacy; Durchmesser Mannloch 510 mm; some residues of previous content; manhole cover is missing; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees

Övrig information2: about the agitator

Omrörare: Ja

Övertryck: 2 Bar

Total urtappning: Ja

Undertryck (vakuum): 0,83 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 8300

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 2.250 mm
Invändig diameter: 1.980 mm
Total höjd: 4.500 mm
Ytterdiameter: 200 mm

Omrörare

Kraft (kW): 2,50
Varvtal: 489

Mer

Isolerad: Ja