

## 885 liter tank i Syrafast 316



**173,000,00 kr /st exkl moms**

**Additional information:** Pharmacy; The previous operator had the vessels hanging in a ring with load cells that was embedded in the ground (1 ring of each is included in the delivery; see photos); Outer diameter in the ring approx. 1,540 mm; insulating jacket made of material 1.0425

**Volumetric volume (L):** 885 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 3 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 130 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 35 L

**Max Overpressure:** 6 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 140 °C

**Type HE on the bottom:** half pipe welded onto the outside of the innertank

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** in the bottom

**Outlet of tank:** 55

**Agitator:** yes

**Number of revolutions:** 416

**Power:** 0,55

**Cylinder:** 6 mm

**Bottom:** 4,50 mm

**Internal diameter tank:** 1.000 mm

**Cylinder height:** 864 mm

**SKU:** 443390

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 130 °C

Mobil tank: Nej

Övrig information: Pharmacy; The previous operator had the vessels hanging in a ring with load cells that was embedded in the ground (1 ring of each is included in the delivery; see photos); we can't give any

Övrig information2: guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 885

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej



## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 864 mm

Invändig diameter: 1.000 mm

## Omrörare

Kraft (kW): 0,55

Varvtal: 416

## Tjocklek på tank

Botten: 4,50 mm

Cylinder: 6 mm

## Mer

Isolerad: Ja