


## 985 liter tank i Syrafast 316



**127,000,00 kr /st exkl moms**

**Additional information:** Pharmacy; Vessel is part of a pharmaceutical plant in a frame, Aisi 304; overall dimensions in the frame are partly estimated and may vary slightly

**Volumetric volume (L):** 985 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 4 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 150 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 82 L

**Max Overpressure:** 6 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 150 °C

**Type HE on the bottom:** heating/cooling jacket

**Type HE on the cylinder:** heating/cooling jacket

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Outlet of tank:** DN50 DIN 11851

**Agitator:** yes

**Power:** 0,55

**Internal diameter tank:** 880 mm

**Outer diameter tank:** 1.000 mm

**Total height of tank:** 2.950 mm

**Total outer width:** 1.400 mm

**Total outer length:** 3.000 mm

**SKU:** 440720

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Pharmacy; Vessel is part of a pharmaceutical plant in a frame, Aisi 304; overall dimensions in the frame are partly estimated and may vary slightly; we can't give any guarantees about the

Övrig information2: heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 4 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 985

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316



## Dimensioner av tank

Invändig diameter: 880 mm

Total höjd: 2.950 mm

Ytterdiameter: 1.000 mm

## Omrörare

Kraft (kW): 0,55

## Mer

Isolerad: Ja