

## 532 liter tank i Syrafast 316



**229,000,00 kr /st exkl moms**

**Additional information:** Full set of pharma-compliant technical documentation included in delivery; tank was manufactured for a global pharmaceutical company but was never put into operation; hand hole with sight glass diameter: 100mm; incl. Südmo single-seat valve SVP (outlet)

**Volumetric volume (L):** 532 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 6 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 150 °C

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 24 L

**Max Overpressure:** 10 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 150 °C

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Outlet of tank:** available

**Top:** 8 mm

**Cylinder:** 5 mm

**Bottom:** 6 mm

**Internal diameter tank:** 800 mm

**Outer diameter tank:** 1.000 mm

**Cylinder height:** 1.040 mm

**Total height of tank:** 1.981 mm

**Empty weight tank:** 800

**SKU:** 440900

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Full set of pharma-compliant technical documentation included in delivery; tank was manufactured for a global pharmaceutical company but was never put into operation; hand hole with sight glass

Övrig information2: diameter: 100mm; incl. Südmo single-seat valve SVP (outlet); we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Övertryck: 6 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Volym i liter: 532

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316

## **Dimensioner av tank**

Cylinderhöjd: 1.040 mm  
Invändig diameter: 800 mm  
Total höjd: 1.981 mm  
Ytterdiameter: 1.000 mm

## **Tjocklek på tank**

Botten: 6 mm  
Cylinder: 5 mm  
Topp: 8 mm

## **Mer**

Isolerad: Ja  
Vikt: 800